

TECHNICAL REPORT

INVESTIGATION OF **ORF/ERPSL TRADEOFFS**



U.S. ARMY INVENTORY RESEARCH OFFICE

AUGUST 1981

ROOM 800 U.S. CUSTOM HOUSE 2nd and Chestnut Streets Philadelphia Pa. 19106

OCT 2 3 1981

A

OTTE FILE COPY

81 10 22

Information and data contained in this document are based on input available at the time of preparation. Because the results may be subject to change, this document should not be construed to represent the official position of the U.S. Army Materiel Command unless so stated.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 2. GOVT ACCESSION NO PROPERTY AND -A 106 001	3. RECIPIENT'S CATALOG NUMBER
TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVER
	Technical Report.
INVESTIGATION OF ORF/ERPSL TRADE OFFS	6. PERPORMING ORG. REPORT NUMBER
· AUTHOR(a)	8. CONTRACT OR GRANT NUMBER(*)
ALAN J. KAPLAN	INO-TH-81.4
PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TAS
US Army Inventory Research Office Room 800 - US Custom House 2nd & Chestnut Sts., Philadelphia, PA 19106	11 (12)29/
11. CONTROLLING OFFICE NAME AND ADDRESS	TE ASPORT DATE
US Army Materiel Development & Readiness Command	Aug 4981
5001 Eisenhower Avenue Alexandria, VA 22333	13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS. (of this report)
	UNCLASSIFIED
	,
	15. DECLASSIFICATION/DOWNGRADING
Approved for Public Release; Distribution Unlimit	15. DECLASSIFICATION/DOWNGRADING
Approved for Public Release; Distribution Unlimit	ed
Approved for Public Release; Distribution Unlimit 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, 11 different in 18. SUPPLEMENTARY NOTES Information and data contained in this docum able at the time of preparation. Because the res this document should not be construed to represent the US Army Materiel Development & Readiness Comm 19. KEY WORDS (Continue on reverse side 11 necessary and identity by block number Multi-Echelon Systems	ment are based on input available to change the official position of land unless so stated.
Approved for Public Release; Distribution Unlimit 17. DISTRIBUTION STATEMENT (of the ebetract entered in Block 20, if different in 18. SUPPLEMENTARY NOTES Information and data contained in this docum able at the time of preparation. Because the res this document should not be construed to represent the US Army Materiel Development & Readiness Comm 19. KEY WORDS (Continue on reverse side if necessary and identity by block number Multi-Echelon Systems Operational Readiness Algorithms	ent are based on input availults may be subject to change the official position of land unless so stated.
16. SUPPLEMENTARY NOTES Information and data contained in this docum able at the time of preparation. Because the resthis document should not be construed to represent the US Army Materiel Development & Readiness Comm 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Multi-Echelon Systems Operational Readiness	tockage of float end items, tional availability. The least cost mix of float and

DD , FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED


403572

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

SECURITY CLASSIF	CICATION OF THIS PAGE(WA	en Date Entered)	 	
{				1
•				
ł				
				- 1
				- 1
!				
}				
				}
	•			1
Į.				j
				- 1
į				į
}				- 1
]				1
				1
ļ				
				}
Ì				Ī
l				1
}				Į.
				ł
}				Í
]				
1				ŧ

TABLE OF CONTENTS

	Page
TABLE OF CONTENTS	1
Introduction	2
Notation	4
Modelling Approaches	5
Relaxation of Assumptions	6
Optimization	7
Analysis of Missile Data	8
APPENDIX I - EXPEDITED RESUPPLY	13
BIBLIOGRAPHY	14
DISTRIBUTION	15



Introduction

Operational Readiness Float (ORF) are end items stocked at Direct Support Units (DSU's) and issued to using units (ORG's) to replace like end items evacuated to the DSU for maintenance. By regulation [11,12], the float end item should not be issued if the evacuated item can be repaired within specified time limits.


Essential Repair Parts Stockage List (ERPSL) are spares and repair parts which are stocked at organizations, direct support units, and possibly other retail echelons to provide a specified degree of end item operational availability. Operational availability is usually defined as the expected percent of time an end item is capable of performing its primary mission. Without ERPSL repair and spare parts are stocked, but not in the same quantity or range.

The interaction between ORF, ERPSL and operational availability is illustrated in Figure 1. When an end item fails, its downtime, if the failure is organization reparable, will depend solely on ORG repair part/spares support. If the end item is evacuated to the DSU, and conditions are met for float issue, then downtime will depend directly on whether a float is available, or on how long it will take to get one. Spare/repair part support at DSU affects operational availability in several ways: if there is no planned DSU float, the user must wait until his evacuated item is repaired; if there is planned float, availability of float for issue will depend on the time to repair evacuated end items as well as on the number of float; and, finally DSU parts support impacts spare/repair part availability to the ORG user.

Currently, ERPSL quantities are developed by computer models which determine the least cost mix of spares/repair parts which are expected to result in a target level of operational availability. The most commonly used model is SESAME [6,10]. Neither SESAME nor any of the other ERPSL models used within the Army allows evacuation of end items from ORG to DSU; hence, they do not model float. SESAME assumes that if a spare must be replaced by DSU-level personnel, a DSU "contact" team can bring the spare to the end item and do the work at ORG.

ORF is currently computed by multiplying specified factors by supported densities. While wartime quantities may be bought, only peacetime levels are actually stocked at DSU's. The peacetime quantity factors are keyed to

METHODOLOGY FLOAT MODEL BASIS



REPAIR LOOP =

(TIME TO RETURN UNIT)

(TIME TO GET SPARE)

(TIME TO INSTALL SPARF)

availability of float [11,12] when needed rather than directly to end item availability at the user. Wartime factors are supposed to be keyed to operational readiness, but the methodology has not been worked out. Repair part support is accepted as a given.

In this paper we discuss techniques for evaluating the operational availability which will be achieved from a given mix of ERPSL and float, and for determining what is the least cost mix to achieve the operational availability target. These techniques are applied to a missile system, which will not be identified since the inputs used were estimates, subject to change, and therefore no longer valid. For the missile system, the error SESAME makes by ignoring float is computed.

Major limitations of this study should be emphasized. The modelling is based on stationary, steady state conditions. Briefly, this means inputs such as densities and average failure rates are not changing over time, and operational availability reflects what will happen, on average, in such an environment. Battlefield surges, disruption of supply, loss of equipment or spares to enemy fire, and so on, are not modelled, nor is the relative vulnerability and mobility of alternative mixtures of ERPSL and ORF considered.

Finally, it should be noted that many of the systems with operational readiness float are not authorized ERPSL. For such systems, the techniques discussed could still be used to determine float quantities, but not to optimize the mix of end item float and spares/repair parts.

Notation

- S Number of float end items per DSU
- MTBF Mean Time Between (end item) Failures
- MTR Mean Time to Repair
- MLDT Mean Logistics Down Time
 - W Average Wait for a float to be available for issue
 - T Time to move a float from DSU to ORG
- PORG Probability a failure can be repaired at ORG
- ORG, DSU Used as subscripts; e.g. MTR_{ORG} is mean time to repair if repair is done at ORG
 - OA Operation Availability
 - Ex() Expected value of variable in parenthesis

MLDT and MTR are defined to be exclusive of each other; MTR assumes the spares/repair parts needed are available, while MLDT refers only to delays to repair caused by absence of parts. MTR_{DSU} includes the time to evacuate the end item to DSU. MLDT_{DSU} refers only to the wait for a part used at DSU, and not to delay in satisfying an ORG requisition on the DSU.

Operational availability is defined as the percent of time an end item is up at ORG. In the event that an end item is evaculated, down time begins when it fails, and up time resumes when the replacement is received.

Modelling Approaches

Initially we will assume failures are stationary Poisson and successive down times are independently and identically distributed; all failures which cannot be fixed at ORG qualify for issue of a float; each failure requires exactly one spare/repair part to be fixed; there is no special treatment of NORS requisitions, i.e. requisitions for a part keeping an end item down at ORG; and there is no cannibalization.

Then

(1)
$$OA = \frac{Ex(Up \ Time)}{Ex(Up \ Time) + Ex(Down \ Time)}$$

$$= \frac{MTBF}{MTBF + (PORG) (MLDT_{ORG} + MTR_{ORG}) + (1-PORG) (T+W)}$$

Note in equation (1) that expected down time is conditional on whether the failure can be fixed at ORG, with probability PORG.

In equation (1), MLDT $_{\rm ORG}$ depends on the ERPSL quantity, while W depends directly on the float stock, S, and indirectly on ERPSL via the impact of ERPSL on MLDT $_{\rm DSH}$.

In particular, if the MLDT's are given, float availability can be modelled as a finite source queue (cf Gross and Harris) and W thereby determined. DSU repairable failures constitute arrivals, and repair constitutes service in queueing terminology. The queue is finite source if the total DSU repairable failure rate depends on the number of operating end items, decreasing as end items go out of service.

While Fox [2] suggested use of the finite source approach for the float problem, it becomes messy if the ORG repairable failures are considered - these

do not constitute demand for float, but do affect the total DSU - repairable failure rate by putting items out of service. Fox did not consider ORG repair. Gross et al [4] present results for a similar problem suggesting that use of an infinite source model is a good approximation. Kaplan [5] provides some sketchy results suggesting that if, in the infinite model, OA is factored into the total estimated failure rate, results improve:

(2) Yearly demand for float = (OA) (Number of Supported End Items) (1/MTBF) (1-PORG)

If there is an OA target, this is used in equation (2). If a given value of S is being evaluated, iteration is employed: assume OA is 85%, and using equation (2) to get the arrival rate, compute W. Use W in equation (1) to develop a new estimate of OA and iterate. The process was programmed to stop after 10 iterations, or when successive values of OA differed by less than 0.5%. The program never took as many as 10 iterations, and the whole process is very fast.

We have been taking MLDT as given. In the SESAME version which is widely distributed, the MLDT which is output is

A modification was made to print out \mathtt{MLDT}_{ORG} and \mathtt{MLDT}_{DSU} separately.

Relaxation of Assumptions

It was assumed that a float would be issued whenever one was needed and was available. However, policy states that a float should not be issued if the evacuated end item can be repaired in a specified number of days, where this number varies among major commands. Such a policy must degrade operational availability in the short run, but offers incentives to organizations to keep their own equipment in the best possible shape.

One method of modelling such a policy is to identify a priori DSU repairable failures which are not serious enough to warrant float issue. For such failures MTR would include time to move the end item to DSU and back, and MLDT would be

If the same part is used at both ORG and DSU, only the ORG demands contribute to MLDT in the distributed version of SESAME.

based on wait for parts at the DSU. Down time would be the sum of MTR and MLDT_{DSU} and would not depend on W (the wait for float).

In the missile analysis it was assumed normal resupply to the ORG from DSU was two days, but that if the part was needed for immediate use on a downed end item, i.e. if there was a NORS requisition, the part could be obtained in one day. Three alternative modifications to SESAME were examined which all gave comparable results. They are discussed in the Appendix.

Optimization

We state the optimization objective as achievement of a given OA target at least cost. The alternative - best possible OA under a given budget constraint - presents no additional difficulties.

The optimization problem was not investigated in the research reported here. A quick and dirty approach was sufficient to do the missile analysis as will be seen. Nevertheless, we would like to briefly discuss the state of the art and a promising approach.

The float problem is a special case of the MODMETRIC problem. The original MODMETRIC model [8] considered situations for which, in our terminology, float could be put at ORG as well as at DSU, but MLDT_{DSU} was fixed and not a decision variable dependent on stockage. In fact, while there now exist a number of MODMETRIC computer programs, the only one which we know of which attempts to optimize MLDT_{DSU} is Clark's [1].

Solution of the MODMETRIC model tends to be time consuming and so various approximate techniques have been developed. Actually no existing code guarantees "the" optimum solution; there are just various degrees of approximation. In the LMI approach to "original" MODMETRIC type problems [9], DSU float and ORG spares are equated in that they indirectly affect OA, while ORG float directly affects OA. (In our version of the problem, with no ORG float, DSU float and ORG spares directly affect OA, while DSU spares indirectly affect OA.)

In the approach to the original MODMETRIC problem most compatible with the SESAME ERPSL program, Kotkin [7] builds on the generalized Lagrangian approach. Given a Lagrangian, spare backorders at ORG are costed out as a weighted average of float cost and the Lagrangian (which is chosen equal to or greater than float cost). The spares problem is solved based on this cost, and then the float stockage problem is solved based on the Lagrangian value, and using the MLDT_{ORG} just found by solving the spares problem. A simple

search routine can be programmed to find the Lagrangian which will produce the target OA.

The ultimate rationale for Kotkin's weighted average formula is that it worked quite well on test cases. However, it was based on a logical derivation. This derivation suggest that the same formula should work equally well in our problem in costing out those DSU backorders for spares which contribute to MLDTDSU. (Some DSU backorders are backorders of replenishment requisitions from the ORG. These backorders are already implicitly and correctly costed out by SESAME as a function of ORG spare backorder cost). The Lagrangian is then used to cost out float and ORG spares backorders.

Analysis of Missile Data

Inputs to the analysis are given in Table I.

Table II evaluates various combinations of ERPSL and float in terms of total cost and operational availability. Float policy I was to stock 85% of the repair cycle quantity for float; the repair cycle quantity is defined as demand per day multiplied by repair time. Float policy II was to stock the entire repair cycle quantity. As it happened, with rounding these two policies gave the same result. Float policy III was to stock sufficient float to satisfy 85% of all demands for float without delay. These policies were based on AR750-1 [12]. Note that the repair cycle quantity depends on the policy for repair parts/spares since the latter impact MLDT_{DSU}.

Under the first policy for repair parts/spares, policy A, there is no ERPSL, but even without ERPSL, repair parts/spares costs, based on standard provisioning procedures, are \$11.6 million for each DSU and its supported ORGs. With zero float, OA = 72.7%, while with 2 float, costing \$2.77 million each, OA increases only to 76.0% and so on.

Note that float does not impact on down time caused by ORG level failures, so that even unlimited float quantities cannot guarantee high OA.

Under stockage policy B, ERPSL is run to achieve a SESAME reported availability of 84.1%. Actual availability without float is 83.4%, and with 1 float, 85.1% OA is achieved. Note that the error SESAME makes in ignoring end item evacuation is not great (84.1% vs 83.4%), nor is the error in ignoring float (84.1% vs 85.1% or 86.6% depending on float policy).

A similar analysis on a limited amount of tank data again showed small errors.

By increasing ERPSL dollars to \$13.0 million (Policy (c)) an OA of 85% is achieved without flost, and at least total cost.

In Table III wartime failure rates were used. Still, no float was cost effective if the OA target were 85%. For a 92% OA target it is cheaper to have 1 float than to increase ERPSL sufficiently to achieve the target without float.

DATA

MTBF

11.5 DAYS (PEACETIME)

4.75 DAYS (WARTIME)

PERCENT OF FAILURES REQUIRING EVACUATION TO DSU: 9.1%

Ĕ

4 HOURS IF ORG REPAIRABLE

30.6 HOURS IF END ITEM IS EVACUATED TO DSU

057'S

DSU -> ORG: 2 DAYS (1 DAY FOR FLOAT OR NORS REQUISITIONS)

CONUS DEPOT - DSU: 32 DAYS

UNIT OF ANALYSIS

1 DSU SUPPORTING 4 ORGS WITH 9 END ITEMS EACH

END ITEM PRICE IS \$2.77 MILLION

TABLE 2

SPARE/FLOAT EVALUATION

		(PEACE	(PEACETIME RATES)		
POLICY	COST SPARES	#/COST FLOAT	TOTAL COST	FLOAT	OPERATIONAL AVAIL
0	11.6 MIL	0	11.6 MIL	10.7 DAYS	72.7%
(NO ERPSL) I	=	2/5.5 MIL	17.1 MIL	3.7 DAYS	76.0%
H	2	5/13.9 MIL	25.5 MIL	0.3 DAYS	77.7%
0	12.6 MIL	0	12.6 MIL	5.3 DAYS	83.4%
(LIMIT I NORS)	3	1/2.8 MIL	15.4 MIL	2.4 DAYS	85.1%
, II	=	4/11.1 MIL	23.7 MIL	0.1 DAYS	86.6
TRADEOFF DERIVED TO GET SS% OP AVAIL	13.0 MIL	O	13.0 MIL	4.4 DAYS	85.1%

TABLE 3

SPARE/FLOAT EVALUATION (WARTIME RATES)

OPERATIONAL AVAIL	92.0%	92.0%
TOTAL COST	41.0 MIL	39.4 MIL
#/COST FLOAT	0	1/2.8 MIL
COST SPARES	41.0 MIL	36.6 MIL
POLICY	NO FLCAT	TRADE OFF DERIVED TO GET 92% OP AVAIL

COMMENTS:

OPERATIONAL AVAIL TARGET WAS RAISED TO 92% ONLY FOR ILLUSTRATION

WITH 85% TARGET, TRADE OFF POLICY SETS ORF TO 0

APPENDIX I

EXPEDITED RESUPPLY

Notation

ORGFILL - ORG fill rate, or fraction of demands filled from stock on hand.

DSUFILL - DSU fill rate.

t - routine supply time

e - expedited supply time

d = t-e

Modelling

SESAME was modified so that item stockage was computed assuming no expedited supply, but ORG LDT was calculated allowing for it. Three alternatives were compared on the missile date:

- a. Reduce LDT by (1-ORGFILL) (d)
- On items not stocked at ORG, reduce LDT by d. On other items,
 reduce LDT by

c. On items not stocked at ORG, reduce LDT by d. On other items reduce LDT by

(1-ORGFILL) (1-DSUFILL) (d) + (1-ORGFILL) (DSUFILL)
$$\frac{d^2}{2t}$$

Rationale. Method c. will be explained, and the other alternatives should then be clear. If an item is not stocked at ORG, then a full d days are saved each time there is a demand. If the item is stocked, but there is no stock on hand, temporarily, there will be due-in. How much time is saved by expediting depends on the status of the due-in. If we could assume, as an approximation, that DSU and ORG on hand status are independent, then with probability (1-DSUFILL)(1-ORGFILL) both ORG and DSU cannot fill a demand, and expediting will save a full d days. If the DSU can fill the demand, and there is one unit due-in uniformly distributed over the interval (0,t), then with probability d/t time will be saved by expediting, and the average saving is d/2.

<u>Comparison</u>. Missile data was run without expedited supply and with the time saving estimted by each of the methods. Results are:

Method	No Expediting	Ā	<u>B</u>	<u>c</u>
LDT	1.8 day	1.47	1.57	1.54

BIBLIOGRAPHY

- Clark, Andrew J., "Logistics Support Economic Evaluation, Optimal Operational Availability Inventory Model," CACI, Arlington, VA, 1978.
- 2. Fox, F., "Determination of the Float Factor By Queueing Theory," US Army Aviation Research & Development Command, St. Louis, 1978, (LD43436MA).
- 3. Gross, Donald and Carl M. Harris, <u>Fundamentals of Queueing Theory</u>, John Wiley, New York, 1974.
- 4. Gross, Donald, Henry D. Kahn and Joseph D. Marsh, "Queueing Models for Spares Provisioning," NRLQ, December 1977, p521ff.
- 5. Kaplan, Alan J., "System Availability With Redundancy and Spares," Army Inventory Research Office, Philadelphia, 1979 (AD-A073743).
- 6. Kaplan, Alan J., "Mathematics of SESAME Model," Army Inventory Research Office, Philadelphia, 1980 (AD-A081931).
- 7. Kotkin, Meyer, "A Heuristic for Multi-Echelon, Multi-Indentured Inventory Problems," Army Inventory Research Office, Philadelphia, 1978 (AD-A066590).
- 8. Muckstadt, Jack, "Model for Multi-Item, Multi-Echelon, Multi-Indenture Inventory System," Mangement Science, Vol 20, December 1973, p472ff.
- 9. Slay, F. M. and T. J. O'Malley, "An Efficient Optimization Procedure for A Levels of Indenture Inventory Model," Logistics Management Institute, Washington, DC, 1978.
- 10. DARCOM Pamphlet No. 700-18, "User's Guide for the Selected Essential Item Stockage for Availability Method," 1980.
- 11. AR 710-2, "Materiel Management for Using Units, Support Units, and Installations," (draft change).
- 12. AR 750-1, "Army Materiel Maintenance Concepts and Policies," May 1978.

DISTRIBUTION

COPIES	
1	Deputy Under Sec'y of the Army, ATTN: Office of Op Reach
	Headquarters, US Army Materiel Development & Readiness Command
1_	DRCDMR
	DRCPS-P, ATTN: Ms. Lamb
<u>_</u>	DRCM
	DRCMM-R
	DRCMM-RS
	DRCMM-M DRCMM-E
	DRCRE
<u>+</u>	DRCDE
	DRCPM
1	Dep Chf of Staff for Logistics, ATTN: DALO-SMS, Pentagon,
	Wash., DC 20310
1_	Dep Chf of Staff for Logistics, ATTN: DALO-SML, Pentagon,
	Wash., DC 20310
1_	Commandant, US Army Logistics Mgt Center, Ft. Lee, VA 23801
1	Office, Asst Sec'y of Defense, ATTN: MRA&L-SR, Pentagon,
	Wash., DC 20310
2	Defense Logistics Studies Info Exchange, DRXMC-D
10	Defense Technical Information Center, Cameron Station, Alexandria,
	VA 22314
	Commander, USA Armament Materiel Readiness Cmd, Rock Island, IL 61299
$\frac{1}{1}$	ATTN: DRSAR-MM
	ATTN: DRSAR-SA Commander, USA Communications-Electronics Cmd, Ft. Monmouth, NJ 07703
1	ATTN: DRSEL-MM
	ATTN: DRSEL-PL-SA
	Commander, USA Missile Command, Redstone Arsenal, AL 35898
1	ATTN: DRSMI-S
1	ATTN: DRSMI-D
	Commander, USA Troop Support & Aviation Materiel Readiness Command,
	St. Louis, MO 63120
1_	ATTN: DRSTS-SPF
1	ATTN: DRSTS-SPS
1_	ATTN: DRSTS-BA
_	Commander, US Army Tank-Automotive Command, Warren, MI 48090
$\frac{\frac{1}{1}}{\frac{1}{1}}$	ATTN: DRSTA-F
	ATTN: DRSTA-S
	Commander, US Army Armament Research & Development Cmd, ATTN: DRDAR-SE, Dover, NJ 07801
1	Commander, US Army Aviation Research & Development Cmd, 4300 Goodfellow
	Blvd, St. Louis, MO 63120
1	Commander, US Army Aviation Research & Development Cmd, ATTN: DRDAV-BD
	(Marl Glenn), 4300 Goodfellow Blvd, St. Louis, MO 63120
1	Commander, US Army Electronics Research & Development Command,
	ATTN: DRDEL-ST-SA, Rm 2D315, Bldg 2700, Ft. Monmouth, NJ 07703
1_	Commander, US Army Mobility Equipment Research & Development Cmd,
	ATTN: DRDME-O, Ft. Belvoir, VA 22060

COPIES	
1	Commander, US Army Logistics Center, Ft. Lee, VA 23801
$-\frac{1}{1}$	Commander, US Army Logistics Evaluation Agency, New Cumberland
	Army Depot, New Cumberland, PA 17070
1	Commander, US Air Force Logistics Cmd, WPAFB, ATTN: AFLC/XRS,
	Dayton, Ohio 45433
1	US Navy Fleet Materiel Support Office, Naval Support Depot,
	Mechanicsburg, PA 17055
1_	Mr. James Prichard, Navy SEA Systems Cmd, ATTN: PMS 3061, Dept
	of US Navy, Wash., DC 20362
1	George Washington University, Inst of Management Science & Engr.,
	707 22nd St., N.W., Wash., DC 20006
1	Naval Postgraduate School, ATTN: Dept of Opns Anal, Monterey,
•	CA 93940
1	Air Force Institute of Technology, ATTN: SLGQ, Head Quantitative
1	Studies Dept., Dayton, OH 43433
$\frac{\frac{1}{1}}{\frac{1}{1}}$	US Army Military Academy, West Point, NY 10996
	Librarian, Logistics Mgt Inst., 4701 Sangamore Rd., Wash.,DC 20016
	University of Florida, ATTN: Dept of Industrial Systems Engr., Gainesville, FL 32601
1	RAND Corp., ATTN: S. M. Drezner, 1700 Main St., Santa Monica,
	CA 90406
1	US Army Materiel Systems Analysis Activity, ATTN: DRXSY-CL,
	Aberdeen Proving Ground, MD 21005
1	Commander, US Army Logistics Center, ATTN: Concepts & Doctrine
	Directorate, Ft. Lee, VA 23801
1_	ALOG Magazine, ATTN: Tom Johnson, USALMC, Ft. Lee, VA 23801
1	Commander, USDRC Automated Logistics Mgt Systems Activity,
	P.O. Box 1578, St. Louis, MO 63188
1	Director, DARCOM Logistics Systems Support Agency, Letterkenny
_	Army Depot, Chambersburg, PA 17201
$\frac{1}{1}$	Commander, Materiel Readiness Support Activity, Lexington, KY 40507
	Director, Army Management Engineering Training Agency, Rock Island
•	Arsenal, Rock Island, IL 61299
$\frac{1}{1}$	Defense Logistics Agcy, ATTN: DLA-LO, Cameron Sta, Alexandria, VA 22314
	Dep Chf of Staff (I&L), HQ USMC-LMP-2, ATTN: LTC Sonneborn, Jr.,
1	Wash., DC 20380 Commander, US Army Depot Systems Command, Letterkenny Army Depot,
	ATTN: DRSDS-LL, Chambersburg, PA 17201
1	HQ, Dept of the Army, (DASG-HCL-P), Wash., DC 20314
1	Operations Research Center, 3115 Etcheverry Hall, University
	of California, Berkeley, CA 94720
1	Dr. Jack Muckstadt, Dept of Industrial Engineering & Operations
	Research, Upson Hall, Cornell University, Ithaca, NY 14890
1	Prof Herbert P. Galliher, Dept of Industrial Engineering,
	University of Michigan, Ann Arbor, MI 48104
1	Scientific Advisor, ATCL-SCA, Army Logistics Center, Ft. Lee, VA
-	23801
	Prof Robert M. Stark, Dept of Stat & Computer Sciences,
•	University of Delaware, Newark, DE 19711
1	Prof E. Gerald Hurst, Jr., Dept of Decision Science, The Wharton
	School, University of Penna., Phila., PA 19104

COPIES	
$\frac{\frac{1}{1}}{\frac{1}{1}}$	Logistics Studies Office, DRXMC-LSO, ALMC, Ft. Lee, VA 23801
1_	Procurement Research Office, DRXMC-PRO, ALMC, Ft. Lee, VA 23801
1	Dept of Industrial Engr. & Engr. Management, Stanford University,
	Stanford, CA 94305
1	Commander, US Army Communications Command, ATTN: Dr. Forry,
	CC-LOG-LEO, Ft. Huachuca, AZ 85613
1	Commander, US Army Test & Evaluation Cmd, ATTN: DRSTE-SY,
	Aberdeen Proving Ground, MD 21005
1_	Prof Harvey M. Wagner, Dean, School of Business Adm, University
_	of North Carolina, Chapel Hill, NC 27514
1	DARCOM Intern Training Center, Red River Army Depot, Texarkana,
-	Tx 75501
1	Prof Leroy B. Schwarz, Pept of Management, Purdue University,
1	Krannert Bldg, West Lafayette, Indiana 47907
$\frac{1}{1}$	US Army Training & Doctrine Command, Ft. Monroe, VA 23651
	Operations & Inventory Analysis Office, NAVSUP (Code 04A) Dept of Navy, Wash., DC 20376
1	US Army Research Office, ATTN: Robert Launer, Math. Div.,
	P.O. Box 12211, Research Triangle Park, NC 27709
1	Prof William P. Pierskalla, 3641 Locust Walk CE, Philadelphia,
	PA 19104
1_	US Army Materiel Systems Analysis Activity, ATTN: DRXSY-MP,
	Aberdeen Proving Ground, MD 21005
	Air Force Logistics Management Center, Gunter Air Force Station, AL 36144
1	ATTN: AFLMC/LGY
$\begin{array}{c} \frac{1}{1} \\ \hline \frac{1}{1} \\ \hline \end{array}$	ATTN: AFLMC/XRP, Bldg. 205
1	Engineer Studies Center, 6500 Brooks Lane, Wash., DC 20315
1	US Army Materiel Systems Analysis Activity, ATTN: Mr. Herbert Cohen,
	DRXSY-MP, Aberdeen Proving Ground, MD 21105
1	Dr. Carl Weisman, C.A.C.I., 1815 North Fort Myer Drive, Arlington, VA 22209
	Commander, US Army Missile Cmd, ATTN: Ray Dotson, DRSMI-DS, Redstone
•	Arsenal, AL 35898
1	Prof Peter Kubat, Graduate School of Mgmt, University of Rochester,
1	Rochester, NY 14627
	Prof Barney Bissinger, The Pennsylvania State University, Middletown, PA 17057
1	Prof Gary D. Scudder, Mgmt Sciences Dept, College of Bus Adm, University
	of Minnesota, 271 19th Ave., South, Minneapolis, MN 55455
	- managed as a sem aver; bounds nameapoute; an 33733

